

# PRODUCT DATASHEET

## LED ECO FLOODLIGHT 70 W 3000 K Gray

LED ECO FLOODLIGHT | LED floodlight luminaires



### Areas of application

- Architectural lighting
- Landscape lighting
- Billboard lighting
- Industrial and storage facilities

### Product benefits

- SMD LED design for high product reliability
- Reduced windage area thanks to slim design
- Frosted cover made of tempered glass for uniform illumination
- Dust and water protection according to IP65

### Product features

- Color rendering index  $R_a$ : > 80
- Luminaire efficacy: up to 85 lm/W
- Die-cast aluminum housing
- Impact resistance: IK06
- Lifetime (L70/B50): up to 30,000 h
- 0.5 m cable between luminaires



## TECHNICAL DATA

### Electrical data


Nominal wattage	70.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	0.90
Protection class	I
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	5670 lm
Luminous efficacy	81 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 5$ sdc <sub>m</sub>
Beam angle	115 °

### Dimensions & Weight

Length	256.00 mm
Width	198.00 mm
Height	35.00 mm
Product weight	1130.00 g
Cable length	500 mm



### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	GLASS

Mercury content	0.0 mg
-----------------	--------


### Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-30...+70 °C
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	All surfaces / Wall
Application environment	Outdoor
LED module replaceable	Not replaceable

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	30000

### DOWNLOAD DATA

DOWNLOAD DATA	
	IES file (IES)

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075230958	Folding box 1	260 mm x 40 mm x 215 mm	1220.00 g	2.24 dm <sup>3</sup>
4058075230965	Shipping box 8	365 mm x 285 mm x 250 mm	10500.00 g	26.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.