



MASTER SON-T PIA Plus

MST SON-T PIA Plus 400W E E40

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Operating Position	UNIVERSAL [Any or Universal (U)]
Cap-Base	E40 [E40]

Light Technical	
Color Code	220 [CCT of 2000K]
Chromaticity Coordinate X (Nom)	0.535
Chromaticity Coordinate Y (Nom)	0.420
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	137 lm/W

Operating and Electrical	
Power Consumption	408.0 W
Voltage (Nom)	105 V
Voltage (Nom)	105 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T46 [T 46mm]


Approval and Application	
Mercury (Hg) Content (Nom)	20 mg
Energy Consumption kWh/1000 h	449 kWh

Product Data	
Full product code	872790095105900
Order product name	MST SON-T PIA Plus 400W E E40
Order code	928144809292
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

MASTER SON-T PIA Plus



Material number (12NC)	928144809292
Full product name	MST SON-T PIA Plus 400W E E40
EAN/UPC - Case	8727900951066

Dimensional drawing



Product	D (max)	O	L	C (max)
MST SON-T PIA Plus 400W E E40	48 mm	83 mm	175 mm	279 mm



Photometric data



Light Distribution Diagram - MST SON-T PIA Plus 400W E E40

Spectral Power Distribution Colour - MST SON-T PIA Plus 400W E E40

Lifetime



Lumen Maintenance Diagram - MST SON-T PIA Plus 400W E E40

Life Expectancy Diagram - MST SON-T PIA Plus 400W E E40

MASTER SON-T PIA Plus

